

K 2000-Series



ONE-PIECE ROTO-MOULD CHASSIS
practically indestructible plastic housing

CONVENIENT INTEGRATED HOSE REEL (TST)
space-saving storage of the high-pressure hose-with foldable crank

ACCESSORY STORAGE
neat storage for high pressure gun and lances

STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

OFF-ROAD CAPABILITY AND STABILITY
robust chassis for easy transport and high stability

604020 K 2160 TST

► **ACCESSORIES** | starting on page 22



EQUIPMENT

- Quick release plug-in system D12
- Total-Stop system
- Pressure regulation
- Cleaning Agent Intake
- Direct suction: Suction height 2.5 m



42251

VARIANT - NON-MARKING

NOM conversion kit Version without drum	Ord.no.	42250
NOM conversion kit Version with drum	Ord.no.	42251
K 2160 TST NOM ex works	Ord.no.	604030

For further information on NON-Marking please refer to page 74

MODEL	K 2160 TS K 2160 TST	K 2100 K 2100T	K 2175 TS K 2175 TST
Ord.no. TS without hose drum	604010	671300	604110
Ord.no. TST incl. hose drum	604020	671310	604120

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-130 3-13	30-100 3-10	30-160 3-16
Water output	l/min l/h	11 660	6.5 390	12 720
Admissible overpressure	bar MPa	150 15	110 10	175 17.5
Motor speed	Rpm	1400	1400	1400
Connection	V ~ Hz A	230 1 50 12.5	110 1 50 15	400 3 50 6.7
Power intake Power output	kW	3.0 2.2	1.7 1.2	3.3 2.6
Power supply cable	m	5	5	5
Dimensions L x W x H	mm	375 360 900	375 360 900	375 360 900
Weight without incl. hose drum	kg	39 40	39 40	39 40

EQUIPMENT

High-pressure hose TS without hose drum	m Ord.no.	10 (DN6) 43416	10 (DN6) 43416	10 (DN6) 43416
High-pressure hose TST incl. hose drum	m Ord.no.	15 (DN6) 48015	15 (DN6) 48015	15 (DN6) 48015
Trigger gun with safety catch	Model Ord.no.	Starlet 4 12525	Starlet 4 12525	Starlet 4 12525
Lance with Vario-Jet Duo	Nozzle Ord.no.	● 042 12433-042	○ 03 12433-03	● 042 12433-042
Lance with Dirtkiller	Nozzle Ord.no.	● 042 12438-042	○ 03 12438-03	● 042 12438-042

