

therm-CA-Series




ACCESSORY STORAGE
neat storage for high pressure gun and lances

REMOVABLE COVERS
convenient and easy service access

CONVENIENT INTEGRATED HOSE REEL (VARIANTE)
space-saving storage of the high-pressure hose - with foldable crank

CONTROL PANEL
analogue temperature regulation

POWERFUL ENTRY MODEL
with all important basic functions



626210 therm-CA 12/150

► **ACCESSORIES** | starting on page 64



EQUIPMENT

- Quick release plug-in system D12
- Total-stop system
- Pressure regulation
- Cleaning Agent Intake
- Locking brake
- Water tank: Volume 3 liters

EQUIPMENT HOT WATER

- Flow monitor
- Combustion chamber pre-ventilation
- Fuel tank: 25 liters



MODEL	therm CA 11/130	
Ord.no. without hose drum	626000	
Ord.no. incl. hose drum	626010	

TECHNICAL SPECIFICATIONS		
Operating pressure	bar MPa	30-130 3-13
Water output	l/min l/h	11 660
Admissible overpressure	bar MPa	145 14.5
Motor speed	Rpm	1400
Connection	V ~ Hz A	230 1 50 13 (NB. supplied with 16 Amp plug)
Power intake Power output	kW	3.0 2.2
Power supply cable	m	5
Dimensions L x W x H without hose drum	mm	860 580 970
Dimensions L x W x H incl. hose drum	mm	860 580 1220
Weight without incl. hose drum	kg	159 164

TECHNICAL DATA HOT WATER		
Hot water output	°C	12-80
Steam level	°C	140
Oil consumption at max. heating output	kg/h l/h	5.1 6.1
Heating oil consumption ΔT 45°	kW	3.2 3.8
Heating output	kW	55

EQUIPMENT		
High-pressure hose without hose drum	m Ord.no.	10 (DN8) 41081
High-pressure hose incl. hose drum	m Ord.no.	20 (DN8) 41083
Trigger gun with safety catch	Model Ord.no.	Starlet 3 12500
Stainless steel lance with flat-jet nozzle	Nozzle Ord.no.	● 045 12420-D25045
Water inlet filter	Ord.no.	13310